

MEZCLADORAS



TURBOMATIC

MEZCLADORAS TIPO TURBINA / TURBINE TYPE MIXERS

Mezcladora tipo turbina de cubeta circular con palas intercambiables y acorazamiento interior, hecho de acero manganeso para una larga duración. Ejes montados sobre chumaceras selladas y sobredimensionadas.

Diseño moderno y efectivo, para el perfecto mezclado de cualquier tipo de inertes, desde polvos hasta hormigones.

Apta para trabajo continuo. Fácil mantenimiento y limpieza.

Mínimo consumo de energía eléctrica. Los datos de este catálogo podrán ser modificados sin previo aviso.

Turbine type mixers with circular bucket, interchangeable blades and internal protection; made of manganese steel for a long-lasting duration. Bearings are mounted on sealed and over-dimensional shafts.

Has a modern and effective design to perfectly mix any kind of materials, from powders to concrete.

Capable to work non-stop, easy cleaning and maintenance; low energy consumption. Data is subject to change without notice



HIDRÓMETRO PARA CONTROLAR AUTOMATICAMENTE LA CANTIDAD DE AGUA EN LA MEZCLA / HYDROMETER TO AUTOMATICALLY CONTROL THE AMOUNT OF WATER IN THE MIX

MODELO/MODEL	TR-60	TR-110	TR-160	TR-220	TR-330	TR-440	TR-550	TR-750
Prod/Lt./min	60	110	160	220	330	440	550	750
Ciclos/hora	50	50	50	50	50	45	45	40
Prod/m ³ /hr	3	5	8	11	16	20	25	30
H.P.	3	5	7.5	10	20	30	40	50
Peso Bruto (kg)	360	570	700	700	850	950	950	1300
Volumen Aprox (m ³)	.80	1	2	2.3	3.5	3.8	4	5
Prod/Gal./min.	15	27.5	40	55	82.5	110	137.5	187.5
Cycles/Hour.	50	50	50	50	50	45	45	40
Prod/CubicYd. /hr.	4	6.5	10.5	14.3	21.0	26.1	32.7	39.2
H.P.	3	5	7.5	10	20	30	40	50
Gross Weight (lbs)	794	1,300	1,885	2,028	3,373	3,725	3,935	4,850
Aprox. Volume Cu. Yd.	1.0	1.3	2.6	3.0	4.5	4.9	5.2	6.5

Tiempo de mezclado 60 Seg. sin carga ni descarga
Mixing Time: 60 Sec. Without loading and unloading.



Atenco 28, Naucalpan de Juárez, Estado de México, C.P. 53348
Tel: 55-5563-5200 Email: ventas@ital.com.mx / www.ital.com.mx